

# Chopped Strand for PA

## ECS301CL

### Identification

**Example :** ECS301CL-3-H  
**ECS :** E-glass Chopped strands  
**Sizing code :** 301CL  
**Chopped length (mm) :** 3  
**Filament diameter :** 10



### Product Description

Standard product for PA6, PA66, applied in automobile, electric products, machine, etc. The series include filament diameter 7μm, specially for low warp and high gloss, FDA approval, NPE free.

### Product Benefits

- Unique surface treatment technology
- Good dispersion
- Low warpage
- High gloss
- Good operability of process
- Resin bond

### Technical Characteristics


Sizing type	Diameter (μm)	Moisture Content (%)	LOI(%)	Bulk Density (g/ cm <sup>3</sup> )
/	ISO 1888	ISO 3344	ISO 1887	ISO 15100
Silane	±1	≤0.05	□0.45±0.1	0.65±0.15

Product code	Glass Type	Filament diameter[μm]	Chopped length [mm]
ECS301CL	ECT	7 10	3、4.5、1.7

## Packing

Packing	Weight [kg]	Bag number per pallet	Palletsize [mm] length*width*height
super-sack	1000	1	1140*1140*1100
paper bag	25	40	850*500*120

## Pallets illustration



Note: Products can be packed according to the customer's request.

## Storage

- If no special requirements, it should be stored in cool and dry place. It is recommended that the temperature control in the 10-30°C, moisture control in 50-75%.
- This product before use should always be placed under the sealed packaging.
- Pallet stacking height should not be more than one layer.



ISO 9001



ISO 14001



OHSAS 18001