

# Chopped Strand for PA

## ECS301HP

### Identification

**Example :** ECS301HP-3-H  
**ECS :** E-glass Chopped strands  
**Sizing code :** 301HP  
**Chopped length (mm) :** 3  
**Filament diameter :** 10



### Product Description

Suitable for PA6, PA66, PA12, PA6T, 9T and other PPA , super glycol and super high temperature resistance; varied rubber modified polyamide; PA blends, such as: PA/PE, PA/PP, PA/ABS. The product in 2010 was named the national industrial products in China and got China Industry Award.

### Product Benefits

- Unique surface treatment technology
- Good dispersion
- Excellent glycol resistance
- Excellent high temperature resistance
- Low warpage
- Low out-gassing
- Good resin bond

### Technical Characteristics


Sizing type	Diameter (μm)	Moisture Content (%)	LOI(%)	Bulk Density (g/ cm3)
/	ISO 1888	ISO 3344	ISO 1887	ISO 15100
Silane	±1	≤0.05	□0.45±0.1	0.7±0.1

Product code	Glass Type	Filament diameter[μm]	Chopped length [mm]
ECS301HP	ECT	10	3、4.5

## Packing

Packing	Weight [kg]	Bag number per pallet	Palletsize [mm] length*width*height
super-sack	1000	1	1140*1140*1100
paper bag	25	40	850*500*120

## Pallets illustration



Note: Products can be packed according to the customer's request.

## Storage

- If no special requirements, it should be stored in cool and dry place. It is recommended that the temperature control in the 10-30°C, moisture control in 50-75%.
- This product before use should always be placed under the sealed packaging.
- Pallet stacking height should not be more than one layer.



ISO 9001



ISO 14001



OHSAS 18001