

Chopped Strand for PA

ECS3014B

Identification

Example : ECS3014B-3-H
ECS : E-glass Chopped strands
Sizing code : 3014B
Chopped length (mm) : 3
Filament diameter : 10



Product Description

For low viscosity PA6 & PA66 as well as rubber modified PA6 & PA66, applied in automobile, electric products, machine, etc. NPE free.

Product Benefits

- Unique surface treatment technology
- Good dispersion
- Excellent integrity
- Good operability of process
- Resin bond

Technical Characteristics


| Sizing type | Diameter (μm) | Moisture Content (%) | LOI(%) | Bulk Density (g/ cm3) |
|-------------|---------------|----------------------|----------|-----------------------|
| / | ISO 1888 | ISO 3344 | ISO 1887 | ISO 15100 |
| Silane | ±1 | ≤0.05 | □0.6±0.1 | 0.60±0.15 |

| Product code | Glass Type | Filament diameter[μm] | Chopped length [mm] |
|--------------|------------|-----------------------|---------------------|
| ECS3014B | ECT | 10 | 3、4.5 |

Packing

| Packing | Weight [kg] | Bag number per pallet | Palletsize [mm] length*width*height |
|------------|-------------|-----------------------|-------------------------------------|
| super-sack | 1000 | 1 | 1140*1140*1100 |
| paper bag | 25 | 40 | 850*500*120 |

Pallets illustration



Note: Products can be packed according to the customer's request.

Storage

- If no special requirements, it should be stored in cool and dry place. It is recommended that the temperature control in the 10-30°C, moisture control in 50-75%.
- This product before use should always be placed under the sealed packaging.
- Pallet stacking height should not be more than one layer.



ISO 9001



ISO 14001



OHSAS 18001