

# Chopped Strand for AS/ABS

## ECS304A

### Identification

**Example :** ECS304A-3-K  
**ECS :** E-glass Chopped strands  
**Sizing code :** 304A  
**Chopped length (mm) :** 3  
**Filament diameter :** 13



### Product Description

Chopped strands for AS/ABS. Applied in automobile, electric products, machine, etc.  
 NPE free

### Product Benefits

- Unique surface treatment technology
- Good dispersion
- Good operability process
- Good resin bond

### Technical Characteristics


Sizing type	Diameter (μm)	Moisture Content (%)	LOI(%)	Bulk Density (g/ cm <sup>3</sup> )
/	ISO 1888	ISO 3344	ISO 1887	ISO 15100
Silane	±1	≤0.05	0.75±0.1	0.70±0.15

Product code	Glass Type	Filament diameter[μm]	Chopped length [mm]
ECS304A	ECT	13	3

## Packing

Packing	Weight [kg]	Bag number per pallet	Palletsize [mm] length*width*height
super-sack	1000	1	1140*1140*1100
paper bag	25	40	850*500*120

## Pallets illustration



Note: Products can be packed according to the customer's request.

## Storage

- If no special requirements, it should be stored in cool and dry place. It is recommended that the temperature control in the 10-30°C, moisture control in 50-75%.
- This product before use should always be placed under the sealed packaging.
- Pallet stacking height should not be more than one layer.



ISO 9001



ISO 14001



OHSAS 18001