

Chopped Strand for MPPO(PPE)

ECS306HR

Identification

Example : ECS306HR-3-K
ECS : E-glass Chopped strands
Sizing code : 306HR
Chopped length (mm) : 3
Filament diameter : 13



Product Description

Standard product for MPPO (PPE), high mechanical properties and excellent hot water resistance. Applied in automobile and electric products. FDA approval and NPE free.

Product Benefits

- Unique surface treatment technology
- Good dispersion
- Excellent glycol resistance
- Excellent hot water resistance
- Good operability process
- Good resin bond

Technical Characteristics


Sizing type	Diameter (μm)	Moisture Content (%)	LOI(%)	Bulk Density (g/ cm ³)
/	ISO 1888	ISO 3344	ISO 1887	ISO 15100
Silane	±1	≤0.05	0.6±0.1	0.65±0.15

Product code	Glass Type	Filament diameter[μm]	Chopped length [mm]
ECS306HR	ECT	13	3

Packing

Packing	Weight [kg]	Bag number per pallet	Palletsize [mm] length*width*height
super-sack	1000	1	1140*1140*1100
paper bag	25	40	850*500*120

Pallets illustration



Note: Products can be packed according to the customer's request.

Storage

- If no special requirements, it should be stored in cool and dry place. It is recommended that the temperature control in the 10-30°C, moisture control in 50-75%.
- This product before use should always be placed under the sealed packaging.
- Pallet stacking height should not be more than one layer.



ISO 9001



ISO 14001



OHSAS 18001