

Chopped Strand for BMC

ECS403W

Identification

Example : ECS403W-3-L
ECS : E-glass Chopped strands
Sizing code : 403W
Chopped length (mm) : 3
Filament diameter : 13.7



Product Description

Designed for BMC processing, applied in ceiling , electric switch, lampshade ,etc..
 Compatible with kinds of resin.

Product Benefits

- Low oil content
- Good appearance
- Good GFRP Coloring
- Perfect GFRP properties
- Compatible for several types of resin

Technical Characteristics


Compatible Resin	Diameter (μm)	Moisture Content (%)	Loss on Ignition (%)	Bulk Density (g/ cm3)
/	ISO 1888	ISO 3344	ISO 1887	ISO 15100
UP、VE、EP、PF	±1	≤0.1	0.8±0.1	±0.15

Product code	Glass Type	Filament diameter[μm]	Chopped length [mm]
ECS403W	ECT	13.7	3、6

Packing

Package Method	Package weight [kg]	Quantity	Pallet size [mm] Length*width*height
Super sack bag	1000	1 pallet	1140*1140*1100
Poly-plastic film bag	25	40 bags	850*500*120

Pallets illustration



Note: Products can be packed according to the customer's request.

Storage

- If no special requirements, it should be stored in cool and dry place .The recommended temperature range is 10-30℃ ,humidity should be 50 -75%.
- The product should be always kept package encapsulation before use.
- Pallet stacking height should not over 1 layer.



FIBERGLASS