

# Chopped Strand for BMC

## ECS404W

### Identification

**Example :** ECS404W-6-L  
**ECS :** E-glass Chopped strands  
**Sizing code :** 404W  
**Chopped length (mm) :** 6  
**Filament diameter :** 13.7



### Product Description

This kind is specially designed for BMC processing. Applied in electronic components, construction pipeline joint ,etc

### Product Benefits

- Good flowability
- Good Compatibility with basic resin
- Excellent mechanical properties
- No yellow fiber

### Technical Characteristics


Compatible Resin	Diameter (μm)	Moisture Content (%)	Loss on Ignition (%)	Bulk Density (g/ cm3)
/	ISO 1888	ISO 3344	ISO 1887	ISO 15100
UP、VE	±1	≤0.1	1.65±0.2	±0.15

Product code	Glass Type	Filament diameter[μm]	Chopped length [mm]
ECS404W	ECT	13.7	6、12、24、48

## Packing

Package Method	Package weight [kg]	Quantity	Pallet size [mm] Length*width*height
Super sack bag	1000	1 pallet	1140*1140*1100
Poly-plastic film bag	25	40 bags	850*500*120

## Pallets illustration



Note: Products can be packed according to the customer's request.

## Storage

- If no special requirements, it should be stored in cool and dry place. The recommended temperature range is 10-30°C, humidity should be 50-75%.
- The product should be always kept package encapsulation before use.
- Pallet stacking height should not over 1 layer.



ISO 9001



ISO 14001



OHSAS 18001